

# Empower your workforce

Tackle the most challenging  
environments with Brother's  
4" mobile label and receipt printer

**RJ-4230B**

[www.brother.eu](http://www.brother.eu)



# Rugged mobile printing

whatever the conditions

RJ-4230B



## Reliable Connectivity

This model provides multiple connectivity options for use in different environments, with USB, Bluetooth (low energy) with MFI capabilities.



## Robust Design

The RJ-4230B is our toughest yet, with an IP54 rating and drop tested up to 2.1 metres, providing the ultimate in durability.



## Easy to deploy

Using the new mobile app, update your printer remotely from any location.



## Easy to use

The LCD screen with menu options make it easy to program, and the backlight ensures you can see it in dark conditions.



## Seamless Integration

Printer drivers are available for Windows OS, and software development kits can be downloaded to support Android and iOS operating systems. ([www.brother.eu/developer](http://www.brother.eu/developer))



## Customisation

We have a wide range of accessories made to suit any environment.



Our RJ-4230B mobile printer is fast, compact and extremely rugged. It empowers workers to operate in any environment with speed, accuracy and efficiency.

It has built-in Bluetooth connectivity, printing up to 4" receipts, quotes, tickets, invoices and labels on demand.





### Warehouse

Shelf edge Labels  
Box Labels  
Delivery Reports

## Vertical Markets

Designed to meet the needs of specialist business sectors



### Logistics & Deliveries

Delivery Report  
Inventory Report  
Invoice



### Ticketing

Parking Notice  
Parking Fine



### Field Sales

Contract  
Quotation  
Receipt  
Product Documentation



### Field Service

Invoice  
Receipt  
Service Documentation  
Contract

## Customise your solution

Brother has designed and engineered a wide range of accessories to meet your specific requirement with a customised solution. Brother accessories are available to enhance your workflow for in vehicle and on body applications.

### Power options & accessories



**PA-BT-006**  
Rechargeable Li-ion smart battery



**PA-AD-600**  
AC adapter  
EU & UK version available



**PA-CD-600WR**  
Permanently wired



**PA-CD-600CG**  
Cigar lighter plug



**PA-CR-002**  
Single charging cradle



**PA-BC-003**  
Single battery charger



**PA-SS-4000**  
Shoulder strap

### Media options



**RD-M01E5**  
Continuous roll  
(Receipt) 101.6mm x 27.7m



**RD-M03E1**  
Label roll  
(72 labels) 101.6mm x 152.4mm

# RJ-4230B Series - Specifications and Features

## Printing / Media

Printing technology	Direct thermal
Print resolution	203dpi
Print speed*	Maximum 127mm/second (5ips)
Maximum print width	104mm
Maximum print length	3000mm
Tear bar	Double
Media width	45-113mm
Roll diameter	58mm max

## LCD

Type	Mono LCD with Back Light
------	--------------------------

## Connectivity

USB	USB version 2.0 (mini-B type)
Bluetooth	Bluetooth Version 4.2 (Low-energy support)
Bluetooth profiles	SPP (Serial Port Profile) OPP (Object Push Profile) HCRP (Hard Copy Cable Replacement Profile) iAP supported
MFi support	Yes
NFC	Yes (Passive)

## General

Operating system support	Microsoft® Windows® 7 / Windows® 8 / Windows® 8.1 / Windows® 10
SDK availability (visit <a href="http://www.brother.eu/developer">http://www.brother.eu/developer</a> )	Brother Print SDK for Android™ (for Android 4.0.3 or later) Brother Print SDK for iPhone/iPad (for iOS 7 or later)
Supported printer commands	P-touch template ZPLII emulation CPCL emulation ESC/P Raster

## Memory

RAM	256MB
Flash	64MB

## Environmental

Drop protection*	2.1 metres
Sealing	IP54
Operating temperature	Operating: -20°C to +55°C / Charging: 0°C to +40°C
Storage temperature	-20°C to 60°C

## Power

Battery (optional accessory)	Rechargeable Li-ion Smart Battery (7.2V)
AC adapter (optional accessory)	110/220V AC (50/60Hz) to 15V DC
Car adapter (optional accessory)	12V DC

## Weights / Dimensions

Dimensions	153(w) x 68(h) x 159(d) mm
Weight (with battery)	850g

### Box Contents

Printer  
Belt clip  
Adjuster guide locks  
Documentation

Contact:

\* Brother standard test environment